

Power Schottky Rectifier - 2Amp 40~200Volt

Features

- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction

Mechanical data

- Case : Molded plastic
- Epoxy : UL 94V-0 rate flame retardant
- Lead : Axial leads, solderable per MIL-STD-202,method 208 guaranteed
- Polarity : Color band denotes cathode end
- Mounting position : Any
- Weight : 0.4 grams

Maximum ratings and Electrical characteristics

Parameters (Note 1)	SB240(E)(H)	SB260(E)(H)	SB2100(E)(H)	SB2150(E)(H)	SB2200(E)(H)	UNIT	
Maximum Recurrent Peak Reverse Voltage	40	60	100	150	200	V	
Maximum RMS Voltage	28	42	70	105	140	V	
Maximum DC Blocking Voltage	40	60	100	150	200	V	
Maximum Average Forward Rectified Current	2					A	
Peak Forward Surge Current	50					A	
Maximum Instantaneous Forward Voltage at 2A	Tc = 25°C	0.55	0.65	0.82	0.88	0.90	V
	Tc = 125°C	0.44	0.50	0.66	0.69	0.72	
Maximum Average Reverse Current at Rated DC Blocking Voltage	Tc = 25°C	0.5		0.05		mA	
	Tc = 100°C	20		10			
Typical Junction Capacitance	150					pF	
Typical Thermal Resistance R _{θJA} (Note 2)	45					°C/W	
Operating and Storage Temperature Range	-50 to +150		-50 to +175			°C	

Note : 1. E means Alloy, H means Halogen-Free

2. Mounted on P.C.B with copper pad size 9.5mm x 9.5mm, vertical P.C.B 9.5mm lead lengths

December 2013 / Rev.7.0

SB240(E)(H) ~ SB2200(E)(H)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-repetitive Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Forward Characteristics




Figure 5. Typical Junction Capacitance



Sirectifier Semiconductor Inc.

U.S.A.: sgc@sirect.com


China: st@sirect.com

Taiwan: se@sirect.com

Hong Kong: hk@sirect.com

SB240(E)(H) ~ SB2200(E)(H)

D0-15



UNIT : inch(mm)